

**SPECIFICATION:**

**MATERIAL**

Insulator: PBT, Rated UL94V-0

Contacts: Brass

CONTACT PLATING:

Underplate: 50m" Nickel

Solder Tails Area: 80m" ~ 120m" Tin/Lead Free(Matte Tin)

**ELECTRICAL**

Operation Voltage: 250 VAC Max.

Current Rating: 3 Amps Max.

Contact Resistance: 30 miliohms Max.

Insulation Resistance: 1000 Megohms Min


Dielectric Withstanding Voltage: 500 VAC / Minute

Operating Temperature: -40°C to +105°C


SPC Type No.	Number of pins	Dimensions					
		A	B	C	D	E	F
SPC15567	28	18.3	18.3	7.62	7.62	7.62	7.62
SPC15568	32	18.0	20.8	7.62	10.16	7.62	5.08
SPC15569	44	23.5	23.5	12.70	12.70	12.70	12.70
SPC15570	68	31.56	31.56	20.32	20.32	20.32	20.32
SPC15571	84	36.66	36.66	25.40	25.40	25.40	25.40

# LAYOUT DIAGRAM


## 20 POSITION



## 28 POSITION




## 32 POSITION




## 44 POSITION



## 52 POSITION



## 64 POSITION



## 84 POSITION

